

# AirSep® NewLife Elite™

STATIONARY OXYGEN CONCENTRATOR

## THE ONE THAT SET THE STANDARDS

Performing in the harshest of environments, this 5 LPM concentrator is simple to service with time-proven quality and reliability.

### • Robust and Easy to Service

The robust Elite is the highest-rated concentrator for efficiency and performance in harsh environments, extreme temperatures, tropical climates, and developing countries where service capabilities are limited. It is also a perfect choice for long term care facilities.

The simplistic internal design makes service and maintenance simple. These workhorse concentrators are a favorite of technicians everywhere.

### • The Most Options For Configuration

Unique to the NewLife® series of concentrators, the Dual Flow option features two separate flow meters that can provide a total of 5 LPMs.

Allowing two patients to get oxygen from one machine at the same time is an ideal solution for hospitals, long term care facilities, clinics, waiting rooms, or day and night time settings.

The Elite can be configured with a  $\frac{1}{8}$  – 2 LPM flow meter for pediatric or low flow uses. If multiple low flow applications are required, the Elite can be combined with the SureFlow™ flow splitting station to serve up to five patients at the same time.

The Elite can also be used to power a handheld nebulizer treatment in place of a compressor with the optional air outlet.



  
**CAIRE**®  
A Chart Industries Company

2200 Airport Industrial Drive, Suite 500  
Ball Ground, GA 30107  
770.721.7759 | Toll Free 1.800.482.2473  
[www.CAIREMedical.com](http://www.CAIREMedical.com)



Copyright 2016 Chart Industries  
ML-CONC0085-EN-GLBL Rev A



## PROVIDER FEATURES

- Highly rated in harsh environments
- Time-proven NewLife ruggedness and reliability
- Easy to service and maintain
- Lockable flow meter
- Dual flow & low flow options
- Dual function hour meter
- Optional Oxygen Monitor

## PATIENT FEATURES

- Resettable circuit breaker
- Direct humidifier bottle attachment
- Smooth & Quiet Operation
- Optional air outlet for nebulizer treatments
- Simple user interface
- Backlined flowmeter for easy viewing

## ORDERING INFORMATION

**NewLife Elite Includes:** Stationary Concentrator, DISS Adaptor Fitting, User Manual

- AS005-1** 120V / 60Hz, USA Cord,
- AS005-4** 120V / 60Hz, USA Cord, O<sub>2</sub> Monitor
- AS005-555** 230V / 50 Hz, EU Cord, O<sub>2</sub> Monitor
- AS005-255** 230V / 50 Hz, UK Cord, O<sub>2</sub> Monitor
- AS005-6** 230V / 60 Hz, EU Cord, O<sub>2</sub> Monitor

*\*other models and country power cords available. Ask about our Dual Flow, Air Outlet, or Low Flow Models\**

## SPECIFICATIONS

|                                    |                                                  |                            |                                                                               |
|------------------------------------|--------------------------------------------------|----------------------------|-------------------------------------------------------------------------------|
| <b>Flow Rates</b>                  | 1.0–5.0 LPM                                      | <b>Storage Environment</b> | –4° to 140°F (–20° to 60°C)                                                   |
| <b>Dimensions</b>                  | 28.5 x 15.7 x 14.5 in<br>(72.4 x 40.0 x 36.8 cm) | <b>Warranty</b>            | 15–95% Humidity<br>3 Years                                                    |
| <b>Weight</b>                      | 54 lbs (24.5 kg)                                 | <b>Maintenance</b>         | Felt Filter (230 V only) – 1 Year Replacement<br>Intake Filter – Clean Weekly |
| <b>Sound Level</b>                 | 48 dB(A)                                         | <b>Maximum Tubing</b>      | 50 ft (15.2 m)                                                                |
| <b>O<sub>2</sub> Concentration</b> | 90% (+5.5% / –3%)                                |                            |                                                                               |
| <b>Operating Environment</b>       | 41° to 105°F (4° to 40°C)<br>15–95% Humidity     |                            |                                                                               |